



RIG #116

RATED TO 7000'

LOCATION SIZE

- 240' x 125'

HYDRAULIC HOIST/MAST

- RATED: 600HP
- CAPACITY 220,000
- DRIVE CAT C16 550 HP
- 2 LINES
- 52'6" STROKE DRILLMEC TELESCOPING
- 1 1/8" DRILL LINE

SUBSTRUCTURE

- THREE AXLE TRAILER CARRIER
- DRILLMEC
- 12' FLOOR HEIGHT
- CLEAR WORKING HEIGHT 10'
- ROTARY CAPACITY 220,000
- PULL DOWN CAPACITY 44,000

TOP DRIVE

- DRILLMEC G-100 HYDRAULIC 110 TON
W/24K FT/LBS OF MAX TORQUE

MUD PUMPS

- (2) IDECO MM550 550HP
- W/(2) C15 CAT 525 HP W/CLUTCH/BELT DRIVE
- 15" STROKE

MUD SYSTEM

- 550 BBLs ONE TANK SYSTEM
- DERRICK SHAKER

BOP/ACCUMULATOR

- 9" REGAN ANNULAR 3K PSI & DOUBLE RAM PREVENTER
- 80 GAL 4 STATION ACCUMULATOR

TABLE

- DRILLMEC 17.5"

IRON ROUGHNECK

- DRILLMEC POWER TONGS
- 6 5/8" MAX DIAMETER, 3 1/2" MIN DIAMETER
- MAX TORQUE 29K FT/LBS MAKE UP
- 40K MAX FT/LBS BREAK OUT

CATWALK

- TRINIDAD RANGE III HYDRAULIC PIPE ARM

WATER TANK

- 450 BBLs CAPACITY

FUEL TANK

- 5000 GAL

POWER

- (2) CAT 3306, 1800 RPM, 225 KW ENGINE/GEN SETS



RIG #116

RATED TO 7000'

